


ARMORED CABLE

Aluminum Interlocked Armor

90°C – 600 Volt

Feeder MC, 4-Conductor



CONSTRUCTION	
Conductor	- Stranded bare copper
Insulation	- Insulated with heat and moisture resistant Cross-linked Polyethylene (XLPE) (type XHHW-2)
Assembly	- Conductors are cabled with suitable fillers if needed and green or bare ground conductor - Cable core is covered with binder tape
Ground	- Green Ground (#8 AWG – #1 AWG) - Bare Ground (1/0 AWG and larger)
Aarmor	- Aluminum interlocked armor
Jacket	- Jacket available upon request.

COLOR CODE CHART

Cond. #	Color
1	Black, Red, Blue, White
2	Black, Red, Blue, White
3	Black, Red, Blue, White
4	Black, Red, Blue, White

Applications:

- Cost effective replacement for conduit and wire
- For service, branch and feeder circuits
- For commercial, industrial & utility applications
- For use in theatres (article 520), motion picture and TV studios (article 530) and places of assembly with more than 100 people.
- Suitable for use in hazardous locations: Class I – Div 2 & Class II – Div 2

Features:

- Temperature Rated at 90°C Wet/Dry

Standards:

- UL 1569
- ICEA S-95-658/NEMA WC-70
- Cable Tray Rated
- NEC Article 330 (can be messenger supported)
- Flame Rated: Two-hour Firewall
- RoHS Compliant

Additional Information:

- Method 4 color code (black, printed number) for 1/0 AWG and larger

Part #	AWG	Pairs	Lbs./M'
1058A	20	12	194

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.