



MEDIUM VOLTAGE POWER CABLE

Single Conductor - EPR Insulation - PVC Jacket

25kV/35 kV, EPR/Copper Tape Shield

UL Type MV-105

133% or 100% Insulation Levels

CONSTRUCTION	
Conductor	• 1/0 AWG thru 1000 kcmil 1350 aluminum compact Class B blocked conductor
Extruded Strand Shield	• Extruded thermoset semi-conducting stress-control layer over conductor
Insulation	• Lead-free Ethylene Propylene Rubber (EPR) insulation, contrasting in color to the black semi-conducting shield layers
Extruded Insulation Shield	• Thermoset semi-conducting polymeric layer free stripping from insulation
Metallic Shield	• 5 mil annealed copper tape with an overlap of 25%
Jacket	• Low-friction, lead-free, flame-retardant, moisture and sunlight-resistant Polyvinyl Chloride (PVC)

Applications:

- Superior performance in petrochemical plants, pulp and paper mills, sewage and water treatment plants, environmental protection systems, railroads, mines, utility power generating stations, steel mills, textile plants and other industrial three-phase applications
- For use in wet or dry locations when installed in accordance with NEC
- For use in aerial, conduit, open tray and underground duct installations
- For use in direct burial if installed in a system with a ground conductor that is in close proximity, and conforms with NEC 250.4(A)(5)

Features:

- Rated at 105°C
- Low friction for easy pulling
- Excellent heat and moisture resistance
- Excellent flame resistance
- Outstanding corona resistance
- Flexibility for easy handling
- High dielectric strength

- Low moisture absorption
- Electrical stability under stress
- Low dielectric loss
- Chemical-resistant
- Meets cold bend test at -35°C
- 105°C rating for continuous operation
- 140°C rating for emergency overload conditions
- 250°C rating for short circuit conditions

Standards:

- National Electrical Code (NEC)
- UL 1072
- ICEA S-93-639/NEMA WC74
- ICEA S-97-682
- AEIC CS8
- UL listed as Type MV-105 for use in accordance with NEC, UL File # E90501
- IEEE 1202 (70,000 BTU/hr)/CSA FT4
- EPA 40 CFR, Part 261 for leachable lead content per TCLP method
- OSHA Acceptable
- RoHS Compliant

Part #	AWG	Conductor Diameter	Insulation Diameter Min.	Insulation Diameter Max.	Jacket Thickness	Nom. O.D.	Lbs./M'
MVA41/001	1/0	.340"	1.02"	1.12"	.080"	1.31"	863

Part #	AWG	Conductor Diameter	Insulation Diameter Min.	Insulation Diameter Max.	Jacket Thickness	Nom. O.D.	Lbs./M'
MVA42/001	2/0	.380"	1.06"	1.16"	.080"	1.35"	925
MVA43/001	3/0	.430"	1.105"	1.205"	.080"	1.40"	863
MVA44/001	4/0	.480"	1.16"	1.26"	.080"	1.45"	1093
MVA425001	250	.530"	1.21"	1.315"	.080"	1.51"	1174
MVA435001	350	.620"	1.31"	1.41"	.080"	1.60"	1356
MVA450001	500	.740"	1.43"	1.53"	.080"	1.72"	1707
MVA475001	750	.910"	1.61"	1.71"	.110"	1.96"	2120
MVA4100001	1000	1.06"	1.76"	1.865"	.110"	2.10"	2500

12-05-2020

*Accessories are available for all medium voltage products.

